

>> Sophisticated Banking Machines for Cash Dispenser Applications

Banking Solutions

ATM 720

The ATM 720 is the latest innovation in the banking product industry. With the integration of the best-in-class modules, ATM 720 is designed to provide sophisticated transactional services with high level of security and lowest down time in the industry maximizing the return on investment.

KEY FEATURES

- Up to 15,000 notes capacity
- Up to 5-cassettes Cash Dispenser Module of 3,000 notes each
- Friction based, high speed notes dispenser (7 notes/second)
- Distribution of notes in Bundle up to 60 notes / operation
- Integrated Reject area built into the first cassette
- Stainless steel anti riot keyboard DES, 3DES, RSA 1024
- Highly reliable -EMV4 - Card Reader for magnetic and smart cards
- 15 " Colour LCD monitor – SVGA
- Industrial, robust PC running under Windows XP Professional
- Integrates most stringent safety standards (UL 291)
- Software built-in WOSA/XFS standards
- NDC, NDC+ full compatibility with enhanced features

Applications

Either using its Open Software Platform or through NDC+, the ATM 720 is designed to support any of the main applications such Withdraw, Inquire Account, Transfer Account or Change PIN's. For advance applications, a long list of options are available built around Bar Code Reader, Passbook printers, Envelope Depositor,



Modern Design

ATM 720 has been designed according to the latest design standards. With its large LCD High Definition display, its anti-riot keyboards RSA1024 compatible and its sophisticated human interface, the ATM 720 contributes to enhance your company image. A list of options such as Touch Screen and Ultra Bright LCD are available to build the exact ATM that matches your specific needs.

Exceptional Reliability and Safety

ATM 720 is designed to match the highest level of safety. Every component or Software has been qualified to the most stringent safety and reliability standards. Its solid safe box is built according to the UL 291 standards. Its double-coded mechanical lock and key insure secure transactional operations. ATM 720 can also be equipped with a sophisticated 3-camera system.

Standards and Software

ATM 720 architecture is based on a industrial PC running under Windows XP Professional and WOSA/XFS standard open platform. The ATM comes with a fully compatible NDC, NDC+ software with some unique enhancements that maximize the remote control of your ATM. Also the products offers facility for advertising and CRM integration.

أجهزة متطورة للبنوك للحصول على النقد

- جهاز سهل الاستعمال ذو قدرة عالية للحصول على النقد
- مناسب للاستخدام في معظم بيئات العمل
- يوفر جميع القدرات والامكانيات للاستخدامات الضرورية
- يعالج المتطلبات والمعاملات اليومية بضمان وسرية تامة

Ways of installation	Through the wall type
Display	<p>Type: 15" High Definition LCD display</p> <p>SVGA resolution : 1024 x 768</p> <p>Brightness: 400 nits - optional Ultra Bright version 1300 nits</p> <p>Number of Colors:16.2M</p> <p>Security: Anti Riot, Dust & Waterproof</p>
Cash dispenser	<p>Type: Friction - High reliable mechanism</p> <p>Speed: Up to 7 notes/second</p> <p>Transaction: Up to 60 notes in one transaction</p> <p>Escrow: Up to 60 notes can be stuck in a bundle</p> <p>Shutter: Electro Mechanical Shutter</p> <p>Reject/Retrieve: Up to 150 notes in a special reject area of first cassette</p> <p>Security: Notes Validation - Width by optical sensors - Thickness by mechanical sensing mechanism</p> <p>Capacity: Up to 5 cassettes - 3000 notes per cassette</p> <p>Denominations: Up to 5 denominations when 5 cassettes are used</p> <p>Notes size: Width: 60~82mm, Length: 120~172mm, Thickness: 0.07~0.18mm</p> <p>Cassette: Locked with one key (optional 2 keys)</p>
Card Reader Module	<p>Type: Motorized, compatible with ISO/IEC standards for transport</p> <p>Functions: ISO standard compliant for magnetic (Track 1, 2 and 3) and chip card (ISO/IEC7816).</p> <p>Shutter: Built-in</p> <p>Reject: Capture box for up to 20 cards</p> <p>Security: Reject Card in case of power interruption</p> <p>Options: Anti-Skimming and Anti-Fishing mechanism.</p>
Keyboard	<p>Type: Anti-Riot, Waterproof Keyboard with 16 keys</p> <p>Material: Stainless steel keys</p> <p>Language: English, Arabic/English, Farsi/English</p> <p>Standards: DES, 3DES, RSA1024, Visa Certified</p>
Controler Unit	<p>Type: Industrial PC located into the safe boxe</p> <p>Operating System: Windows XP Professional</p> <p>CPU: Intel® Pentium® 4 2.4GHZ</p> <p>BIOS: AMI PnP BIOS, 2 M capacity, with power supply management and virus warning.</p> <p>Memory: high performance DDR memory, 512 MB</p> <p>Hard disk: High-speed EIDE Hard disk, UDMA66 certified, 80 GB</p> <p>Display: AGP ,CRT/ LCD accelerator</p> <p>Interface: Ethernet 10/100 base T, 2 x serial interface, 1 x parallel interface, 1 x USB</p> <p>Extended bus: 2 x PCI extension bus</p> <p>External Devices: Floppy &/or CD-R/W</p>
Supervisor Terminal	<p>Type: Text Terminal Unit NDC+ compatible</p> <p>Inputs: 20 keys and 8 function keys</p> <p>Display: 5" Color LCD</p>
Connectivity	<p>Standard: Modem - Serial Interface for Modem supporting up to 128k bauds Ethernet connection through</p> <p>Optional: GPRS X.25 or SNA</p>
Receipt Printer	<p>Technology: thermal printer</p> <p>Width: 8 dot/mm, 576 dot/line, 72mm (32 character per line)</p> <p>Speed: approx. 90mm/sec</p> <p>Paper: Thickness: 0.07-0.12 mm, external diameter of the paper roll: 128 mm</p> <p>Security: Programmable Paper near detection & Paper empty detection</p>
Journal printer	<p>Technology: Bi-directional impact printer (9-pin print head)</p> <p>Width: 8 dot/mm, 210dot/line, 63mm (40 character per line)</p> <p>Speed: 3.1 line per second</p> <p>Paper: The 0.07-0.12 mm, 85 mm external diameter</p> <p>Security: Programmable Paper near detection & paper empty detection</p>
Safe Box	<p>Standard: Safe box corresponds to UL 291 standards</p> <p>Security: Key and Double Coded mechanical lock</p>
Lead Through indicators	Highly visible green lead through indicators for Card Reader and Receipt
Power	<p>Inputs: 205 – 245 V , 50 Hz</p> <p>Option: Uninterrupted Power Supply allows during power cut to complete current transaction before shutting down the ATM.</p>
Operating Environment	<p>Temperature: -30^o to 45^o C (outdoor), 0^o to 40^o C (indoor), 0^o to 50^o C (Storage)</p> <p>Humidity: 20-95%</p>
Dimensions & Weight	740 x 1050 x 1720 mm (W x D x H), Weight: 650 Kg

Software Environment**NDC/NDC+ Software****Standard:** ISO 8593, WOSA/XFS, NDC/NDC+, Diebold**Full online Transaction, configuration and download support for NDC ATM System**

NDC 6.04 – NDC 7 functionality

Diebold 910/911 and 920/921

Aptra Advance NDC 2.04 functionality (*)

EMV Level 1 and 2 certified

Support latest EMV2000 specifications, DES, 3DES

TCP/IP and Dial-up support

SNA and X.25 (*)

Terminal Controller Support (RTC)

Security Features

SSL, VPN or IPSEC on IP based system

Remote Key Management (*)

3DES and EMV compliance

Complete ATM software and operating system lock-down

Supervision Applications

Secure Key Entry

Terminal Balancing

Settlement and Reporting (*)

Cash Replenishment and collection (*)

Rear Access Support

Electronic Journal (EJ) with file update

Access to system trace data

Full audit capabilities

Additional Features (*)

WEB-enabled and HTML screen support

MStatus ad XFS status sent to Host for monitoring

Software distribution

Advertising and CRM integration support

Ping function

(*) Features available with fully featured license software.

Options

- Additional Cassettes,
- UPS (Uninterrupted Power Supply),
- Touch Screen Monitor,
- Camera,
- Bar code Reader,
- NDC module,
- Envelop Deposit Unit,
- Passbook printer,
- Temperature Control Device.

For more information:**Head office**100 Alexis Nihon Blvd., Suite 250, Montreal, Quebec, Canada H4M 2N7
Tel.: (514) 855-4994 | Fax: (514) 855-0541 | info@globalis.com**Gulf, Near East,
Iran & CIS**Al-Khaleej Bldg., Office 307, Zabeel Road
P.O. Box: 52460, Dubai, U.A.E.
Tel.: (971-4) 334-6700 | Fax: (971-4) 334-6912 | info-dubai@globalis.com**Egypt**44 Abdel Moneim Riad Street, Office 32, Mohandseen, Giza, Egypt
Tel.: (20-12) 780-0613/4 | Fax: (20-2) 304-6718 | info-egypt@globalis.com**Maghreb countries**100 Alexis Nihon Blvd., Suite 250, Montreal, Quebec, Canada H4M 2N7
Tel.: (514) 855-4994 | Fax: (514) 855-0541 | info-maghreb@globalis.com

globalis
international

www.globalis.com