

>> **Powerful 1800 lpm bilingual speed, unmatched durability and optimized performance that satisfy the needs of large industries and financial institutions**

Bilingual Dot Matrix Printer

cima 5180

Increase productivity and reduce costs with Globalis' Cima 5180a line printer that combines next-generation speed and leading built-in Arabization to blaze through the most demanding print jobs.



KEY FEATURES

- Ultra-fast speed of 1800 lpm
- Built-in Arabization with complete support for Arabic standards
- Integrated IBM Arabic Support
- Industry's only lifetime warranty on shuttle mechanism
- Platform independent: Unix, VMS, Windows
- Text mode support for Windows 9x/NT/2000/XP
- Hot-port switching of all ports
- Stores up to 10 user-defined forms
- More than 18 bar code styles
- Four-tractor mechanism (six pins engaged), for the best paper-handling
- Quietized cabinet model available
- Ideal for data processing, industrial graphics, multipart forms, labels, orders and invoices

Guaranteed reliability

Globalis Cima 5180a printer offers high print speeds reaching 1800 lines per minute in both Arabic and Latin languages, with the best transparent Arabization support.

The printer is designed to handle tough print jobs with its unique two-tier print modules that enable continuous printing in case one tier fails. The Cima 5180a legendary reliability, paper sensors, ribbon life monitor feature, and the industry's only lifetime warranty on the shuttle mechanism provide peace of mind.

Ease of use

Operating a printer has never been easier with the Cima 5180a user-friendly control panel, which has raised buttons for a practical access to the logical menu structure. This heavy-duty printer protects your budget with its low-cost consumables, user-replaceable print heads and maintenance-free operation that keep cost of ownership low. Both its standard and quietized cabinets are easy to install and are designed with an outstanding durability that best fit your office requirements.

طابعات السطور الثنائية اللغة

- تتميز هذه المجموعة من الطابعات بسرعة طباعة عالية باللغتين العربية واللاتينية
- تعتمد على طريقة غلوباليس الخاصة للمعالجة الشفافة لخصائص اللغة العربية
- تقدم الدعم الشامل لمقاييس اللغة العربية
- تعمل ضمن نظام التشغيل Windows, Unix وتقدم الدعم الكامل لبيئات العمل IBM Mainframe
- تضم مجموعة من الأطقم العربية واللاتينية
- تجمع بين التكنولوجيا، الدقة في الأداء والجودة في الطباعة والمتانة العالية لمساعدتكم على مواكبة التطور

Print technology	Line impact dot matrix
Print speed	Draft 1800 lpm EDP 1400 lpm DP 1350 lpm NLQ 410 lpm
Character sets	Host code sets: ASMO-449/449+, ASMO-708/708+, ARCII, ASCII, DEC/8/ASMO, Al-Arabi, Mussaed Al-Arabi, IBM APC/XBASIC/Cobra/Genilink, CODAR-UFD, ICL CODAR, ICL ASMO-708, ICL Cross Range, NCR 64/96, NCR ASMO-708, Data General, HP Arabic-8, HP Enhanced, Comterm 341/348/541, Integro 708 UNIX, ASMO/French, French/ASMO, User-defined PC Code Sets: ADOS-708, ADOS-709, ADOS-711, ADOS-720, ADOS-864, ADOS-710/96, Arabic Windows 1256
Fonts	Draft, data processing, correspondence, Gothic NLQ, Courier NLQ, Italic NLQ, OCR-A, OCR-B, PC graphics, Greek/Math symbols
Bar codes	Interleaved 2 of 5, Bi-directional 2 of 5, Matrix 2 of 5, Industrial 2 of 5, Code 3 of 9, EAN-8/13, Code 11, Code BCD, Codabar A/B/C/D, UPC-A/E, Code 93, Code 128 (A-B-C), Royal mail, Postnet
Graphics	Vertical: 72 or 144 dpi; Horizontal: 60, 120, or 240 dpi Formats: Printronix P300/600, ANSI X3.64, line draw and block PC graphics, dot-addressable graphics
Print modules	2x66 pins (6 modules)
Print characteristics	Vertical spacing: 3, 4, 6, 8, plus user selectable; Horizontal spacing: 10, 12, 13.3, 16.7, 17.1, 20 cpi plus user selectable Print line length: 13.6 in.
Print control	EVFU (12 and 14 channels); Form length to 22 inches; Store up to 10 user-defined forms; Auto perf skip-over feature Horizontal tabs: 22 positions; Vertical tabs: absolute or relative
Print modes	Oversize, bold, underline, superscript/subscript, proportional, expanded and download characters
Paper handling	Width: 7.6 to 42 cm; Number of copies: original + 5; Up to 120-lb cardstock/110 index (125 tag); Paper slew: 10/20 ips
Sensors	Paper out, paper jam, ribbon jam, print gap
Emulation	ANSI X3.64 enhanced, IBM Proprinter III XL, Epson FX-286e, Epson ESC P/2, Printronix P Series, P300/600 SCS only: Coax- IBM models 6408, 3287, 4234; Twinax- IBM models 5225, 4234, 6408 IPDS only: Coax- 4234/6408, 3287; Twinax- 4234/6408, 5225
Interface and connectivity	Parallel port: IEEE 1284; Serial port: RS-232/422 Optional port I/O (2 slots): Twinax/coax (one board per printer); choice of SCS or IPDS; coax cable and self-terminating twinax T connector are included with board, Ethernet 10/100BaseT, Ethernet 10BaseT/2, Legacy parallel for older hosts with non-standard parallel interfaces
Memory	8 Mb standard
Drivers	Windows 9x, 2000, NT 4.0
Reliability	MTBF: 8,000 hours at 25% duty cycle
Consumables	Type: Black ribbon cartridge Life: 50 million character or 125 million character with internal reinking; "Clean hands" installation
Physical	Dimensions (w x d x h): Standard cabinet: 737 x 635 x 1219 mm; Quietized cabinet: 760 x 725 x 1080 mm Weight: Standard cabinet: 145 kg; Quietized cabinet: 191 kg
Operating environment	Temperature: 4° to 46°C (operating); Humidity: 10-90%, non-condensing; Acoustics: 55 dBA standard cabinet, 52 dBA quietized cabinet; Voltage: 120 and 240 V switchable; Power consumption: 50 watts (idle), 674 watts (printing), 1167 watts (max); Energy Star: Yes
Warranty	Standard one-year; Lifetime warranty on shuttle mechanism

For more information:

Head office	100 Alexis Nihon Blvd., Suite 250, Montreal, Quebec, Canada H4M 2N7 Tel.: (514) 855-4994 Fax: (514) 855-0541 info@globalis.com
Gulf, Near East, Iran & CIS	Al-Khaleej Bldg., Office 307, Zabeel Road P.O. Box: 52460, Dubai, U.A.E. Tel.: (971-4) 334-6700 Fax: (971-4) 334-6912 info-dubai@globalis.com
Egypt	44 Abdel Moneim Riad Street, Office 32, Mohandseen, Giza, Egypt Tel.: (20-12) 780-0613/4 Fax: (20-2) 304-6718 info-egypt@globalis.com
Maghreb countries	100 Alexis Nihon Blvd., Suite 250, Montreal, Quebec, Canada H4M 2N7 Tel.: (514) 855-4994 Fax: (514) 855-0541 info-maghreb@globalis.com



globalis
international

www.globalis.com