

Continuous Laser Printer

Professional continuous forms laser printing
at price performance never known before.



CF 32

The CF 32 is the first Fanfold-Laser Printer that can offer an affordable replacement solution to the Line Printer application providing the high quality of laser printers while offering a competitive cost of ownership.

Key Features

- Print speed reaching 32 ppm at 600 dpi resolution
- Up to 200 000 pages monthly workload
- SAP & AS/400 compatible
- Powerful controller providing special functions such as: internal form management, n-times format splitting, SPS-Control
- USB, Ethernet, parallel IEEE 1284 and serial (RS 232/RS 422)
- Various types of built-in barcodes
- Outstanding low cost per page
- Optional MICR Support
- Suitable for Retail, Banking and Finance industries, Warehouses and governmental departments.

Innovative features

The CF 32 continuous laser printer features a robust engine for trouble-free continuous printing up to 200,000 pages per month. This new engine provides a breakthrough evolution in cost per page guaranteeing the best price/performance ratio in the industry.

In addition, the CF 32 integrates a High-End Controller allowing internal form management, n-time format splitting and SPS-control. All this is supported by a 600x600 dpi resolution which differentiates the printer from all the line printer categories available in the market.

Maximum performance at minimum costs

The CF 32 offers complete connectivity and emulations as standard. Additional emulations are available as option and cover most of the legacy environments and therefore a simple plug and play replacement to old line printers.

The printer comes with a push tractor that could handle a wide variety of paper formats without any problems. Furthermore, its logic control panel allows simple selection from several alternative user configurations. The CF 32 is the first high speed continuous form laser that offers high print quality at an affordable price.

Secure Printing with "SafePrint" Software

Also available on Al Khattat CF family the newly announced SafePrint software that manages your print jobs and secures your printing. This powerful software can be used to cluster several printers when very large print jobs need to be run in an unattended environment. The software will automatically split the job to the available printers and monitor every single printed page. If jam occurs or printer stops, the software will report the exact information related to the non printed page. SafePrint can be set-up to automatically back-up the job to one of available printers and resumes from the very specific page where previous printing stopped.

This new and unique feature provides administrator with a high level of security when printing critical output such as customers' statements.

globalis
international

www.globalis.com

Print technology	Laser, OPC, Heat/Pressure Fixing
Print speed	32 pages per minute (A4 landscape)
Engine speed	6.9 m/min.
Print resolution	600 x 600 dpi
Duty cycle	200,000 pages/month (based on a using period of 60 months)
Media handling	Length: 3 to 33 in. Width: 6.5 to 15 in. Printable width: 13.6 in Weight: 60-160g/m2 Input tray 1: Push Tractor Output Tray (Option): Stacker, Cutter
Barcodes	EAN-8, EAN-13, EAN-128, 2/5 3-stroke Datalogic, 2/5 3 stroke Matrix, Codebar, PDF 417, Jetcaps (HP/SAP), Code 39, 128 MSI, UPC A, UPC E, Postnet, KIX.
Optional Barcodes	USD5, Datamatrix, UPS-Maxicode (more barcodes on the request)
Interface & connectivity	Serial: USB, RS232, RS422 Parallel: IEEE 1284 Parallel bi-directional, LAN: Ethernet 10/100 baseT,
Emulations	Epson F X-80, IBM Proprinter, Diablo 630, TIFF, ZPL, micro-Postscript, HP PCL 5e, Microplex
Optional emulation	Printronix IGP, PGLP, Datamax, ZPLII, Magnum Code Y, Kyocera Prescribe, Express
Memory	RAM: 64 MB, Flash: 16 MB
Functions	Internal barcodes generation Intelligent form management : up 12MB Flash for forms and fonts inside the printer Format splitting : in several subformats by command
Optional functions	Status out : gives notice of each correctly printed page via interface
Warm up time	3 min. after power on, 15 sec warm
Main consumables	Toner kit: 2 cartridges - 64,000 pages each cartridge @ 4% coverage with optional MICR support Developer Unit Waste Bottle OPC Drum Developer Mix Kit
Physical	609 x 609 x 419 mm
Weight	61 Kg (including consumables)
Operating environment	Temperature: 10° to 32° C Humidity: 20 to 80% Acoustic Level: < 55dB(A) Power Supply: 230V +/-10% /50 Hz
Warranty	Standard one-year

For more information:

Head office	100 Alexis Nihon Blvd., Suite 405, Montreal, Quebec, Canada H4M 2N9 Tel.: (514) 855-4994 Fax: (514) 855-0541 info@globalis.com
Gulf, Iran & Pakistan	Al-Khaleej Bldg., Office 307, Zabeel Road P.O. Box: 52460, Dubai, U.A.E. Tel.: (971-4) 334-6700 Fax: (971-4) 334-6912 info-dubai@globalis.com
Levant & Maghreb	Garden Tower, Office 9A Antelias, Beirut, Lebanon Tel.: (961-4) 414-248 Fax: (961-4) 414-842 info-beirut@globalis.com info-maghreb@globalis.com
Egypt	3 Mohamed Abdel Salam Street, off Abdel Aziz Fahmy, 1st Floor, Apt. 2 Heliopolis, Cairo, Egypt Tel.: (20-12) 780-0613/14 Fax: (20-2) 2638-4850 info-egypt@globalis.com
Saudi Arabia	Al Takhassousy St. Riyadh, KSA Tel.: (966-55) 377-6788 Fax: (971-4) 334-6912 info-saudi@globalis.com

