

Best price performance and unmatched durability that satisfy the needs of various industries and institutions.

cima 6120/6060

Increase productivity with the cima 6120/6060 line printers that accommodate the most demanding applications in the harshest environments. With their rugged and efficient design, they provide the most reliable and economical printing solutions.



KEY FEATURES

- High print speeds reaching 1200 lpm (6120) and 600 lpm (6060)
- Remarkable print capacity reaching 345 000 pages/ month
- Straight paper path with 2-tractors system for jam-free operation
- Platform independent: Unix, VMS, Windows
- Twinax, Coax, Ethernet, IPDS and IPDS over TCP/IP
- Quick change, clean-hands ribbon cartridges
- Automatic Print Gap adjustment with "Clean hand", long life cartridge ribbon
- Read/right bar code algorithm for high quality bar codes
- Consistent print density with exclusive "SmartRibbon" technology
- Life time warranty on shuttle mechanism
- 250 million character life ribbon, the longest in their category
- Integrated Web page for a user friendly interface

Guaranteed reliability

Globalis cima 6120/6060 printer offer high print speed reaching 1200 lpm (6120) and 600 lpm (6060). this series is designed to provide the essential reliability and durability to industries, thanks to the Automatic print adjustment and easy load paper system that allow minimal operator intervention.

User-friendly features

The cima 6100 series are capable of printing large amounts of data keeping cost of ownership low with its maintenance-free operation, low-cost consumables, user-replaceable print heads, and "Clean Hands" concept for ribbon replacement. Furthermore, the user-friendly control panel and logical menu structure ensure easy manipulation of any printing application.

A Cost saving solution

The Globalis cima 6120/6060 line printers series offer first class performance with consumables at very low cost ownership. Both 60 and 250 million character ribbons provide a consistent supply of ink resulting a uniform output and an excellent printing quality.

Print technology	Line impact dot matrix												
Print speed (in draft mode)	<table border="1"> <tr> <td></td> <td>6120</td> <td>6060</td> </tr> <tr> <td>Draft (@10 cpi)</td> <td>1200 lpm</td> <td>600 lpm</td> </tr> <tr> <td>DP (@10 cpi)</td> <td>900 lpm</td> <td>450 lpm</td> </tr> <tr> <td>Gothic (@ all cps)</td> <td>378 lpm</td> <td>189 lpm</td> </tr> </table>		6120	6060	Draft (@10 cpi)	1200 lpm	600 lpm	DP (@10 cpi)	900 lpm	450 lpm	Gothic (@ all cps)	378 lpm	189 lpm
	6120	6060											
Draft (@10 cpi)	1200 lpm	600 lpm											
DP (@10 cpi)	900 lpm	450 lpm											
Gothic (@ all cps)	378 lpm	189 lpm											
Character sets	<p>Host code sets: ASMO-449/449+, ASMO- 708/708+, ARCII, ASCII French A/B/Canadian, DEC/8/ASMO, Al-Arabi, Mussaed Al-Arabi, Sakhr, Nafitha, Jiskas, Ameer, Behive, Citoh, IBM APC/XBASIC/Cobra/Genilink, CODAR-UFD, ICL CODAR, ICL ASMO-708, ICL Cross Range, NCR 64/96, NCR ASMO-708, Data General, HP Arabic-8, HP Enhanced, Comterm 341/348/ 541, Integro 708 UNIX, ASMO/French, French/ASMO, User-defined.</p> <p>PC Code Sets: ADOS-708, ADOS-709, ADOS-711, ADOS-720, ADOS-864, ADOS-710/96, Arabic Windows 1256</p>												
Fonts	Draft, data processing, Gothic, Courier, OCR-A, OCR-B												
Character styles	Bold, italic, superscript, subscript, underline, overline, strike through												
Bar codes	Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, Code 39/128, PDF417, UPC-A, Codabar, MSI, POSTNET, Idensticon 2 of 5												
Graphics	<p>Vertical: 288 dpi; Horizontal: 240 dpi;</p> <p>Formats: Printronix® PGL, QMS® CODE VTM Version 2</p>												
Workload	6120a: 345 000 pages/month, 6060a: 175 000 pages/month												
Character printing modes	Constant density fonts, enhanced fonts, 13 pitches ranging from 5 to 20 cpi												
Print characteristics	<p>Lines Per Inch: 1.5, 2, 3, 4, 5, 6, 8, 9, 10 & 12 cpi</p> <p>Characters Per Inch: 5, 6, 6.7, 7.5, 8.3, 8.6, 10, 12, 13.3, 15, 16.7, 17.1, 20 cpi</p> <p>Print line length: 13.6"</p>												
Paper handling	<p>Width: 3" to 18.7"; Length: 1 to 255 lines</p> <p>Forms thickness: maximum .025", Weight: 15 to 100 lbs. stock</p>												
Paper advance	Slew Speed: 25 inches per second												
Memory	32 Mb. standard												
Multi-part stationary	Up to 6 part forms, Automatic Gap Adjustment												
Emulation	ANSI, IBM Proprinter III XL, Epson FX-1180, Printronix® P600 & P 5000/6000, DEC® LG01, HP 2564C, Tally line/dot matrix printer Epson FX 1180, MTPL, contextual Arabic, Twinax (IBM 4234/4210/5225)/Coax(IBM4234), HP LineJet HPLP Series, HP 256X												
Interface & connectivity	Parallel port: IEEE 1284; Serial port: RS-232 with 38.4K baud transfer												
Optional interfaces	<p>FourPlex I/O: Twinax, coax, serial & parallel, IPDS for LAN</p> <p>LANPlex I/O: Ethernet (10Base-T/100Base-T), IPDS for LANPlex</p>												
Consumables	<p>6060a: 40 M.Characters, 6120a: 40, 60, 250 M. Characters</p> <p>Type: Easy-load, smartRibbon® cartridge</p>												
Physical	<p>Dimensions (w x d x h): 28.5" x 23.5" x 40" (pedestal mounted version), 28.3" x 14.4" x 13.0" (Table Top version)</p> <p>Weight: 53 kg (table top version), 73 kg (pedestal version)</p>												
Operating environment	<p>Temperature: 10°C to 40°C (operating), -40° to 66°C (non-operating), Humidity: 10-90% non-condensing (operating), 5% to 95% non-condensing (non-operating), Acoustics (open/enclosed pedestal): 6060a: 55/52 dB(A), 6120a: 60/<55 dB(A),</p> <p>Voltage: 90-130 / 180-264 V, Frequencies: 50/60 Hz (auto-ranging), Energy star: Yes</p>												
Warranty	Standard one-year												

For more information:

Head office	100 Alexis Nihon Blvd., Suite 405, Montreal, Quebec, Canada H4M 2N9 Tel.: (514) 855-4994 Fax: (514) 855-0541 info@globalis.com
Gulf, Iran & Pakistan	Al-Khaleej Bldg., Office 307, Zabeel Road P.O. Box: 52460, Dubai, U.A.E. Tel.: (971-4) 334-6700 Fax: (971-4) 334-6912 info-dubai@globalis.com
Levant & Maghreb	Garden Tower, Office 9A Antelias, Beirut, Lebanon Tel.: (961-4) 414-248 Fax: (961-4) 414-842 info-beirut@globalis.com info-maghreb@globalis.com
Egypt	3 Mohamed Abdel Salam Street, off Abdel Aziz Fahmy, 1st Floor, Apt. 2 Heliopolis, Cairo, Egypt Tel.: (20-12) 780-0613/14 Fax: (20-2) 2638-4850 info-egypt@globalis.com
Saudi Arabia	Al Takhassousy St. Riyadh, KSA Tel.: (966-55) 377-6788 Fax: (971-4) 334-6912 info-saudi@globalis.com



globalis
international

www.globalis.com