

>> **Compact printer for general purpose and specific applications**

Dot Matrix Printers



impact 1170+

Globalis Impact 1170+ comes in a compact design and prints up to 505 characters per second at very low noise level.

This flatbed heavy duty printer is ideal for business applications as well as industrial environment offering an all-in-one solution for transactional single sheet applications as well as continuous form printers with outstanding multi-copy capability.

KEY FEATURES

- Print speed up to 505 cps
- Print head life of 300 million character
- Up to 7 copies
- 24-needle print head with 5 million draft characters life
- Up to 128 Kb input buffer
- 8 barcode types
- Flexible, intelligent printer that can be used for front desk applications
- Bi-directional printing with logic seeking
- Standard Parallel, serial or Parallel, USB interface
- Suitable for transaction applications
- Integrated LAN (option)
- Available with built-in Arabization for full Arabic standard support

Flexible paper handling

Great paper handling ability with a capacity to print continuous forms up to 7 copies. The 1170+ features flexible and configurable paper handling to facilitate paper manipulation in transactional environment. It offers also a reliable support of continuous forms. The printer can print on a variety of papers, envelopes, postcard, adhesive strips and multiple copy forms.

The printer comes with a parallel interface and can be equipped with an optional serial or USB interface. It integrates popular emulations to support a variety of environments.

Outstanding performance

The Impact 1170+ printer is designed to offer the best print techniques for a good quality output at a minimum cost. It delivers the same quality output on single sheets as on multiple copy forms up to 1+7

Print Technology	24-pin, serial impact dot matrix															
Print speed	<table border="1"> <thead> <tr> <th></th> <th>HSD</th> <th>Draft</th> <th>NLQ</th> <th>LQ</th> </tr> </thead> <tbody> <tr> <td>12 cpi</td> <td>505 cps</td> <td>440 cps</td> <td>220 cps</td> <td>110 cps</td> </tr> <tr> <td>10 cpi</td> <td>460 cps</td> <td>409 cps</td> <td>170 cps</td> <td>92 cps</td> </tr> </tbody> </table>		HSD	Draft	NLQ	LQ	12 cpi	505 cps	440 cps	220 cps	110 cps	10 cpi	460 cps	409 cps	170 cps	92 cps
	HSD	Draft	NLQ	LQ												
12 cpi	505 cps	440 cps	220 cps	110 cps												
10 cpi	460 cps	409 cps	170 cps	92 cps												
Character sets	Arabic code sets: ASMO-449/449+, ASMO-708/708+, ARCII, ASCII, DEC/8/ASMO, Al-Arabi, IBM APC, XBASIC, CODAR-UFD, ICL, CODAR NCR ASMO-708, Cross Range, NCR 64/96, Data General, HP Arabic-8, HP Enhanced, Comterm 348/ 541, CITO, Ameer, Integro 708 UNIX, ASMO/French, French/ASMO, ADOS-708/709/710/711/720/128/864/96, Mussaed Arabi, Arabic Windows 1256, User-defined															
Operating mode support	8-bit Arabic pure with neutrals, GLCCs, & GLCCs balancing 7-bit Arabic with GLCCs, GLCCs balancing & escape sequences															
Arabic fonts	Draft, Courier Naskh, High Draft															
Character sets	Standard ASCII character set, Italic Pc437, Pc850, etc., 15 internal character sets															
Fonts	Draft, courier, Prestuge, High draft, PICA, OCR-A, OCR-B, Bold face, Correspondance															
Bar codes	Code 3 of 9, UPC Type A, Code 128, EAN13, PostNET, Interleaved 2 of 5, matrix 2 of 5 EAN 8, codbar (NW7), UPC Type A with check character															
Print characteristics	Width: Cut sheet: 50-350 mm Continuous paper: 50-350 mm Print length: 14.3 inches Paper weight :60 tp 110 gms per square meter Thickness: 0.06 to 0.58mm															
Number of copies	Original + 7 copies															
Number of columns	110 col.															
Paper insertion	Cut sheet: Front in/Front out, and Front in/Rear out Continuous: Rear in/Front out															
Throughput	HS Draft mode : 350 Pages Draft mode : 320 Pages															
Emulations	Epson LQ series, Epson FX286e, IBM ProprinterXL24/24 e, ANSI, HP															
Interface and connectivity	Parallel, serial or Parallel, USB Optional: Ethernet 10/100 Base T connector type RJ-45 (Internal)															
Input data buffer	128Kb															
Consumables	Type: Black ribbon cartridge; 5 million characters															
Print head life	300 million character															
MTBF	15,000 hours															
Physical	Size (w x d x h): 475 x 350 x 215 mm Weight: 9 kg															
Operating environment	Temperature: Operating: 5° to 35° C; Storage: -20° to 60°; Humidity: 20% to 80% (operating); Consumptions: 12W to 47W; Acoustics: 58 dBA; Voltage: 220V, 165 to 264 VAC; Frequency: 49.5 to 60 Hz															
Warranty	Standard one-year															



For more information:

Head Office	100 Alexis Nihon Blvd, Suite 405, Montreal, Quebec, Canada H4M 2N9 Tel.: (514) 855-4994 Fax: (514) 855-0541 info@globalis.com
Gulf, Near East, Iran & CIS	Al-Khaleej Bldg., Office 307, Zabeel Road P.O. Box: 52460, Dubai, U.A.E. Tel.: (971-4) 334-6700 Fax: (971-4) 334-6912 info-dubai@globalis.com
Egypt	3 Mohamed Abdel Salam Street, off Abdel Aziz Fahmy, 1st Floor, Apt. 2 Heliopolis, Cairo, Egypt Tel.: (20-12) 780-0613/14 Fax: (20-2) 2638-4850 info-egypt@globalis.com
Maghreb Countries	100 Alexis Nihon Blvd, Suite 405, Montreal, Quebec, Canada H4M 2N9 Tel.: (514) 855-4994 Fax: (514) 855-0541 info-maghreb@globalis.com

globalis
international

www.globalis.com