

>> **Compact printer for general purpose and specific applications**

Dot Matrix Printers

impact 1175

Globalis Impact 1175 comes in a compact design and prints up to 480 characters per second at very low noise level.

This heavy duty printer is ideal for business applications as well as industrial environment offering an all-in-one solution for transactional single sheet applications as well as continuous form printers with outstanding multi-copy capability.

KEY FEATURES

- Print speed up to 480 cps
- Up to 5 copies
- 24-needle print head for high quality printing
- Flexible paper handling for ease of use
- 10 barcode types
- Bi-directional printing with logic seeking
- Standard Parallel and optional serial or network interface
- Suitable for transaction and front desk applications
- Integrated LAN (option)
- Available with built-in Arabization for full Arabic standard support

Flexible paper handling

Great paper handling ability with a capacity to print continuous forms up to 5 copies. The 1175 features flexible and configurable paper handling to facilitate paper manipulation in transactional environment. It offers also a reliable support of continuous forms. The printer can print on a variety of papers, envelopes, postcard, adhesive strips and multiple copy forms.

The printer comes with a parallel interface and can be equipped with an optional serial or network interface. It integrates popular emulations to support a variety of environments.

Outstanding performance

The Impact 1175 printer is designed to offer the best print techniques for a good quality output at a minimum cost. It delivers the same quality output on single sheets as on multiple copy forms up to 1+4 copies.

Print Technology	24-pin,serial impact dot matrix															
Print speed	<table border="1"> <thead> <tr> <th></th> <th>HSD</th> <th>Draft</th> <th>NLQ</th> <th>LQ</th> </tr> </thead> <tbody> <tr> <td>12 cpi</td> <td>480 cps</td> <td>432 cps</td> <td>270 cps</td> <td>135 cps</td> </tr> <tr> <td>10 cpi</td> <td>400 cps</td> <td>360 cps</td> <td>225 cps</td> <td>113 cps</td> </tr> </tbody> </table>		HSD	Draft	NLQ	LQ	12 cpi	480 cps	432 cps	270 cps	135 cps	10 cpi	400 cps	360 cps	225 cps	113 cps
	HSD	Draft	NLQ	LQ												
12 cpi	480 cps	432 cps	270 cps	135 cps												
10 cpi	400 cps	360 cps	225 cps	113 cps												
Character sets	Arabic code sets: ASMO-449/449+, ASMO-708/708+, ARCII, ASCII, DEC/8/ASMO, Al-Arabi, IBM APC, XBASIC, CODAR-UFD, ICL, CODAR NCR ASMO-708, Cross Range, NCR 64/96, Data General, HP Arabic-8, HP Enhanced, Comterm 348/ 541, CITO, Ameer, Integro 708 UNIX, ASMO/French, French/ASMO, ADOS-708/709/710/711/720/128/864/96, Mussaed Arabi, Arabic Windows 1256, User-defined															
Operating mode support	8-bit Arabic pure with neutrals, GLCCs, & GLCCs balancing 7-bit Arabic with GLCCs, GLCCs balancing & escape sequences															
Arabic fonts	Draft, Courier Naskh, High Draft															
Character sets	Standard ASCII character set, Italic Pc437, Pc850, etc., 15 internal character sets															
Fonts	Draft, courier, Prestuge, High draft, PICA, OCR-A, OCR-B, Bold face, Correspondance															
Bar codes	Code 3 of 9, UPC Type A, Code 128, EAN13, PostNET, Interleaved 2 of 5, matrix 2 of 5 EAN 8, codabar (NW7), UPC Type A with check character															
Print characteristics	Vertical spacing: 6, 8, 12 lpi; 3, 4, 6, 8, 12 lines per 30 mm; Incremental (inches): n/60, n/72, n/216, n/180, n/360 Horizontal spacing: 5, 6, 7.5, 8.5, 10, 12, 15, 17.1, 20, 24 and proportional Print line length: 13.6 in															
Print resolution	Vertical: 60, 72, 180, 360 dpi Horizontal: 60, 80, 90, 120, 180, 240, 360 dpi															
Paper handling	Paper Width: 4 to 10.5 in Paper Length : 14.3 inches Paper weight : 60 tp 110 gms per square meter Max. Thickness: 0.36mm															
Number of copies	Original + 4 copies															
Number of columns	80 col.															
Paper insertion	Cut sheet: Top in/Top out Continuous: Rear in/Rear out															
Throughput	HS Draft mode : 350 pph Draft mode : 320 pph															
Emulations	Epson LQ Series, Epson FX286e, IBM ProprinterXL24/24E , ANSI, HP, DPL24C+															
Interface and connectivity	Parallel: Centronics IEEE 1284 36-pin amphenol; Max. speed: 1000Kbytes/sec Serial: RS-232C Speed up to 38,400 baud Optional: USB, Ethernet 10/100 Base-T connector type RJ-45															
Input data buffer	128Kb															
Consumables	Type: Black ribbon cartridge; 5 million characters															
Print head life	300 million characters															
MTBF	20,000 hours															
Physical	Size (w x d x h): 415 x 330 x 120 mm Weight: 7.39 kg															
Operating environment	Temperature: Operating: 5° to 38° C; Storage: -15° to 60°; Humidity: 30% to 80% (operating); Consumptions: 10W to 70W; Acoustics: 49 dBA; Voltage: 220V, 165 to 264 VAC; Frequency: 49.5 to 60 Hz															
Warranty	Standard one-year															



For more information:

Head Office	100 Alexis Nihon Blvd, Suite 405, Montreal, Quebec, Canada H4M 2N9 Tel.: (514) 855-4994 Fax: (514) 855-0541 info@globalis.com
Gulf, Near East, Iran & CIS	Al-Khaleej Bldg., Office 307, Zabeel Road P.O. Box: 52460, Dubai, U.A.E. Tel.: (971-4) 334-6700 Fax: (971-4) 334-6912 info-dubai@globalis.com
Egypt	3 Mohamed Abdel Salam Street, off Abdel Aziz Fahmy, 1st Floor, Apt. 2 Heliopolis, Cairo, Egypt Tel.: (20-12) 780-0613/14 Fax: (20-2) 2638-4850 info-egypt@globalis.com
Maghreb Countries	100 Alexis Nihon Blvd, Suite 405, Montreal, Quebec, Canada H4M 2N9 Tel.: (514) 855-4994 Fax: (514) 855-0541 info-maghreb@globalis.com

globalis
international

www.globalis.com