

>> Ultra High Speed Serial Matrix Printer For Heavy Workload

Dot Matrix Printer



impact 4900

With the highest speed in the market, Globalis Impact 4900 is aimed at heavy applications while offering a low cost of running and excellent reliability over the years.

KEY FEATURES

- Ultra High Speed - 1630 cps at 10 cpi with good print quality
- Built-in Arabization with complete support for Arabic standards
- Remarkable print capacity reaching 60,000 pages/month
- Workhorse for heavy load
- Low running cost
- Long life consumables
- Straight paper path with 2 tractor system for jam-free operation
- Compatible with the industry's environments
- Multiple connectivity

An outstanding printer

The Impact 4900 breaks record. With the highest printing speed in both Arabic and Latin languages for a serial printer, the impact 4900 is a fast printer designed to sustain heavy workload while offering a low running cost. The printer offers a very high reliability in the toughest environments. A set of connectivity options is available (Parallel and Serial are standard, while USB and Ethernet are optional), and the printer comes with a full support for various environments (Windows, Unix, Novell, DOS, SAP and IBM System).

Ease of use

The Impact 4900 maximizes productivity. A user friendly operator panel with LCD, long life ribbons that are easy to replace and auto gap adjustment make the printer simple to use and reliable over long printing jobs.

Low cost of ownership

The impact 4900 offers an unbeatable low cost of ownership with long life consumables.

globalis
international

www.globalis.com

Print technology	impact dot matrix
Bilingual print speed	1,630 characters per second @ 10 cpi
Character sets	Host code sets: ASMO-449/449+, ASMO-708/708+, ARCII, ASCII French A/B/Canadian, DEC/8/ASMO, Al-Arabi, Mussaed Al-Arabi, Sakhr, Nafitha, Jiskas, Ameer, Behive, CitoH, IBM APC/XBASIC/Cobra/Genilink, CODAR-UFD, ICL CODAR, ICL ASMO-708, ICL Cross Range, NCR 64/96, NCR ASMO-708, Data General, HP Arabic-8, HP Enhanced, Comterm 341/348/541, Integro 708 UNIX, ASMO/French, French/ASMO, User-defined. PC Code Sets: ADOS-708, ADOS-709, ADOS-711, ADOS-720, ADOS-864, ADOS-710/96, Arabic Windows 1256
Arabic Fonts	Variety of Arabic fonts
Latin Fonts	Draft, data processing, Gothic, Courier, OCR-A, OCR-B
Bar codes	Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, Code 39, PDF417 2 dimensional, UPC-A, UK Post Office Matrix 2 of 5, with read/write algorithm
Graphics	Vertical: 288 dpi; Horizontal: 240 dpi; Formats: Printronix® PGL, QMS® CODE V™ Version 2
Workload	60,000 pages/month
Character printing modes	Constant density fonts, enhanced fonts, 13 pitches ranging from 5 to 20 cpi
Print characteristics	Lines Per Inch: 1.5, 2, 3, 4, 5, 6, 8, 9, 10 & 12 cpi Characters Per Inch: 5, 6, 6.7, 7.5, 8.3, 8.6, 10, 12, 13.3, 15, 16.7, 17.1, 20 cpi Print line length: 13.6"
Paper handling	Width: 2.5" to 17.25" (65mm to 438mm); Length: 1 to 255 lines, Forms thickness: maximum 0.025" (0.635mm) Weight: 65 to 365 gsm STD Paper handling: 65 2 tractors, 36 inches (914mm) per second (fast slew), 25 inches (365mm) per second (default slew)
Multi-part stationery	Up to 6 part forms, Automatic Gap Adjustment
Emulation	ANSI, IBM Proprinter III XL, Epson FX-1180, MTPL
Interface & connectivity	Parallel port: IEEE 1284; Serial port: RS-232 with 38.4K baud transfer
Optional interfaces	Ethernet, USB (Plug in module)
Consumables	Ribbon Life: 25 million characters
Physical	Dimensions (w x d x h): 720 x 442 x 330 mm Weight: 53 kg (table top version), 73 kg (pedestal version)
Operating environment	Temperature: 10°C to 40°C (operating), -40° to 66°C (non-operating) Acoustics: 52 dB(A) Voltage: 90-264 V; Frequency: 47/63 Hz
Warranty	Standard one-year

For more information:

Head office	100 Alexis Nihon Blvd., Suite 405, Montreal, Quebec, Canada H4M 2N9 Tel.: (514) 855-4994 Fax: (514) 855-0541 info@globalis.com
Gulf, Iran & Pakistan	Al-Khaleej Bldg., Office 307, Zabeel Road P.O. Box: 52460, Dubai, U.A.E. Tel.: (971-4) 334-6700 Fax: (971-4) 334-6912 info-dubai@globalis.com
Levant & Maghreb	Garden Tower, Office 9A Antelias, Beirut, Lebanon Tel.: (961-4) 414-248 Fax: (961-4) 414-842 info-beirut@globalis.com info-maghreb@globalis.com
Egypt	3 Mohamed Abdel Salam Street, off Abdel Aziz Fahmy, 1st Floor, Apt. 2 Heliopolis, Cairo, Egypt Tel.: (20-12) 780-0613/14 Fax: (20-2) 2638-4850 info-egypt@globalis.com
Saudi Arabia	Al Takhassousy St. Riyadh, KSA Tel.: (966-55) 377-6788 Fax: (971-4) 334-6912 info-saudi@globalis.com



globalis
international

www.globalis.com