

>> Modern, Stylish Kiosk for Mutli-Purpose Applications

Self Terminal Solutions

K2000



The new K2000 Kiosk integrates in a modern device high quality components to support a wide range of solutions for Banks, Public or Private applications. The K2000 is modular to be adapted exactly to the customer requirements.

VALUE AND QUALITY FEATURES

- Compact and Fashion Design
- Ideal for Self Terminal Applications
- EMV4 compliant for financial applications
- Modular Design
- Integrated Multimedia feature (sound/image)
- WOSA / XFS Level 3 compliant



Configuration (Base):

Host (CPU based on Celeron 2.0GHz)
Touch Screen 15" LCD Display - Anti Vandal
Sound Device
Receipt Printer
Motorized Card Reader
Metal Keyboard (anti vandal, water & dustproof)

Options

Optional Keyboard (EPP) DES, 3DES
Tracking Ball
Bar Code Scanner
Invoice Printer
Anti Vandal Telephone
Contactless IC card reader
Bill Validator (on project basis)
Communication interface (GPRS,...)
Higher specs Host PC

Ways of installation	Lobby-Style
Host	Celeron 2.0GHZ CPU DDR 256M Memory Hard disc: 40 GB Integrated Sound card, Loudspeaker 2 parallel ports, 6 USB 2.0 ports, 6 Serial Ports Network card: TCP/IP protocol 10/100 MB 1 PS2 keyboard ports, 1 Mouse Port
LCD Monitor	15" LCD DPI: 1024 x 768 Color: 16.2M Lightness: >300 cd/m ² Contrast: 300:1 Interface: VGA
Motorized Card Reader	Interface: RS232 TK1+2+3 reading and IC Card read/write Optional: EMV4.0 certified Magnetic card: ISO 7811 standard IC smart card: ISO 7816 (T = 0 & T = 1) CPU card reader; Card return when power failure, Card capture bin
Anti-Vandal Touch Screen	Life-span: 50 million (touch the same point) Accuracy rate: 99% Anti-Vandal, waterproof, dust proof, scratchproof
Metal Keyboard	Hardware encryption PIN-Pad Support DES, 3 DES 16 keys and 8 function keys Anti-Vandal, waterproof, dust proof
Receipt Printer	82 mm thermal printer Volume diameter: >150 mm Print speed: max 125mm/s Print density: 200 DPI Interface: RS232/Parallel Auto-Cutting, paper empty & paper low detection, blacklist detection
Laser Bar Code Scanner	Bar code: 1C bar code Bar code standard: UPC-A, UPC-E, EAN-8, EAN-13, Code 39, Code 93, Code 128, Interleaved 2 of 5, Discrete 2 of 5, Codabar MSI Bar code print contrast: 39 ± 3 t/s Scanning angle: 53° Obliquity: 55° Bevel: 65°
Power	Output power: 220VAC ± 20% (176VAC ~ 264VAC) Voltage: 24V, 5A Frequency: 49 Hz ~ 51 Hz
Operating Environment	Temperature: 0° C ~ +50° C Humidity: 40% - 80%
Dimensions & Weight	Dimensions: 520 mm x 450 mm x 1602 mm (W x D x H) Weight: 100 Kg

Options

- LCD Barcode Scanner
- Contactless Card Reader
- Tracking Ball
- Invoice Printer
- UPS
- 8 PSAM Card
- Communication (GPRS & CDMA)
- Antivandal Telephone
- Touch Screen
- Bill Validation (on project basis)

For more information:

Head office	100 Alexis Nihon Blvd., Suite 272, Montreal, Quebec, Canada H4M 2N7 Tel.: (514) 855-4994 Fax: (514) 855-0541 info@globalis.com
Gulf, Near East, Iran & CIS	Al-Khaleej Bldg., Office 307, Zabeel Road P.O. Box: 52460, Dubai, U.A.E. Tel.: (971-4) 334-6700 Fax: (971-4) 334-6912 info-dubai@globalis.com
Egypt	3 Mohamed Abdel Salam Street, off Abdel Aziz Fahmy, 1st Floor, Apt. 2 Heliopolis, Cairo, Egypt Tel.: (20-12) 780-0613/14 Fax: (20-2) 2638-4850 info-egypt@globalis.com
Maghreb countries	100 Alexis Nihon Blvd., Suite 272, Montreal, Quebec, Canada H4M 2N7 Tel.: (514) 855-4994 Fax: (514) 855-0541 info-maghreb@globalis.com