ReceiptNOW® Teller Receipt Printers





ReceiptNOW printers add thermal receipt printing to your check scanner. Engineered to fit underneath Digital Check® SmartSource® or TellerScan® scanners, the stackable design allows users to combine their scanner and receipt printer into the desktop footprint of a single device.







CUSTOMIZE RECEIPTS

ReceiptNOW printers enable users to customize the look and feel of their receipts. Options include top and bottom logos, border messages, watermarks, and Windows TrueType fonts.

STACKABLE

DESIGN OPTIONS

ReceiptNOW printers are engineered to fit beneath your check scanner so you can enjoy a cleaner, more efficient workspace. ReceiptNOW is available in two form factors, each designed to fit beneath a range of SmartSource and TellerScan products.

KEY FEATURES & BENEFITS

- > USB and Optional **Ethernet Connection** Ports
- > Modular Design Saves Counter Space
- > Easy Slide-Out Drawer for Paper Replacement
- > Economical and Easy Thermal Printing
- > Print Graphics on Your Receipts
- > Engineered for Durability



- USB or optional Ethernet interface
- Full 108 standard and international fonts with barcode
- Compatible with international power standards
- Worldwide certifications



USB AND/OR ETHERNET CONNECTIVITY

The ReceiptNOW printer offers flexibility for different environments. This printer includes options for both Ethernet and USB-connected configurations.



FEATURES

- Quiet thermal receipt printer
- Frees up teller space
- Simple pull-out, drop-in paper
- Fits the largest receipt paper
- Full or partial paper cut



Headquarters & Americas Operations







Let's get in touch!

Technical Specifications ReceiptNOW®

Printer Dimensions

ReceiptNOW Elite

Height 5.7 in (14.48 cm) **Width** 5.3 in (13.46 cm) **Length** 10.5 in (26.67 cm)

ReceiptNOW (original)

Height 5.4 in (13.72 cm) **Width** 6.1 in (15.5 cm) **Length:**15.3 in (38.86 cm)

Printing / Feed / Cut

Direct Thermal Printer
Maximum print speed is 250mm/sec.
(ReceiptNOW Elite)
Resolution: 203 x 180 dpi
95 Alphanumeric, 13 International Characters with
Kanji TrueType Fonts available when being driven
as a Windows printer
1D/2D Bar Code Fonts
512K On-board Logo Flash
Full/Partial Auto Cutter

Controls

On/Off Switch
Paper Empty/Low LEDs with audible alerts
Paper Feed Button
Paper Width Adjustment

Paper Width Adjustment

Power Indicator

Paper / Loading

Standard, Security, Non-BPA, 2-color Paper **Paper Widths** 2.4 in to 3.25 in (6.1 cm to 8.3 cm) **Paper Roll Diameter** 3.25 in (8.3 cm) Slide Out Tray, Drop-in Paper

Supported Operating Systems

Windows 11, Windows 10 (32/64 bit)

Interface

USB and/ or Ethernet (ReceiptNow Elite)
USB only (ReceiptNow Original)
Standard ESC/POS Command Set
OPOS & JavaPOS, Auto Status Back (ASB)

Included Accessories

USB 2.0 cable (ReceiptNow Elite USB or Ethernet & ReceiptNow (original))
1 ft. Ethernet cable (ReceiptNow Elite Ethernet)
International 100-240VAC, 50/60Hz power supply

Graphic Receipt Customization

Multiple Graphics Can be Placed Anywhere Custom Messages Watermarks

Environmental

Operating Temperature 41° - 104° F (5° - 40° C) Operating Humidity 20 - 90% non-condensing

Certifications

Safety UL, cUL, CE **Emissions** FCC: Class B, ICES-003, CE, VCCI **Power Supply Efficiency** DOE Level VI RoHS Compliant



Part Numbers

SRNELITE-USB (ReceiptNOW Elite with USB)
SRNELITE-ETH2-E (ReceiptNOW Elite, USB & Ethernet)
SRN2PTR-USB (ReceiptNOW Original with USB)



ReceiptNOW EliteUSB and/or Ethernet
Configurations



ReceiptNOW (original) USB Configuration







Headquarters & Americas Operations



