

Impact 1170

Dotmatrix Printer

- › Compact printer for general purpose and specific applications.



All-in-one solution for transactional single sheet applications, as well as continuous form printers with outstanding multicopy capability.

Applications

The Impact 1170 flatbed printer is ideal for business applications as well as industrial environment.

Outstanding performance

It comes in a compact design and prints up to 415 characters per second at very low noise level.

The 1170 is designed to offer the best print techniques for a good quality output at a minimum cost. It delivers the same quality output on single sheets as on multiple copy forms for up to 1+6 copies.



Key Features

- › Print speed up to 415 cps.
- › Print head life of 250 million strokes/wire
- › Up to 7 copies.
- › 24-needle print head with 5 million draft characters life.
- › Up to 64 Kb input buffer.
- › 8 barcode types.
- › Flexible, intelligent printer that can be used ffront desk applications.
- › Bi-directional printing with logic seeking.
- › Standard Parallel, optional serial or USB interface.
- › Suitable for transaction applications.
- › Integrated LAD (opcion).
- › Available built-in 864 Arabic code page.



Let's get in touch!
info@globalis.com

Headquarters &
Americas Operations

www.globalis.com

Middle East, Africa
& Asia Operations

www.alistech.ae

Technical Specifications Impact 1170

Flexible paper handling

Great paper handling ability with a capacity to print continuous forms up to 7 copies including the originals. The 1170 features flexible and configurable paper handling to facilitate paper manipulation in transactional environment. It also offers a reliable support of continuous forms. The 1170 can print on a variety of papers, envelopes, postcards, adhesive strips and multiple copy forms. It comes with a parallel interface and it can be equipped with an optional serial or USB interface. It integrates popular emulations to support a variety of environments.

Technical Specifications

Print Technology

24-pin, serial impact dot matrix

Print speed

10 CPI

HSD: 379 cps

Draft: 309 cps

NLQ: 206 cps

LQ: 103cps

Character Sets

- 8-bit Standard ASCII character set, Italic PC437, PC850, etc.
- 15 international character sets
- 864 Character set.

Latin Fonts

Draft, Roman, Sans Serif, OCR-A, OCR-B, etc.

Barcodes

8 types including EAN-13, Code 39, Code 128

Print Characteristics

Width: Cut sheet: 50-350 mm
Continuous paper: 50-350 mm

Length (Cut sheet): <59 mm

Thickness: 0.06 to 0.58 mm

Number of Copies

Original + 6 copies

Number of Columns

110 col.

Paper Insertion

Cut sheet: Front in/Front out
Front in/Rear out

Continuous: Rear in/Front out

Emulations

Epson ESC P, OKI

Interface & Connectivity

PAR/USB/NIC.

Input data buffer

64 Kb

Consumables

Type: Black ribbon cartridge

Life: 5 million characters

Print Head Life

250 million strokes per wire

MTBF

10,000 hours

Physical

Dimensions (w x d x h):

475 x 350 x 215 mm

Weight: 9 Kg

Operating Environment

Temperature: Operating: 5° to 35° C ; Storage: -20° to 60°

Humidity: 20% to 80% (operating)

Consumptions: 12W to 47W

Acoustics: 58 dBA

Voltage: 220V, 165 to 264 VAC

Frequency: 49.5 to 60 Hz

Warranty Standar one-year



Let's get in touch!
info@globalis.com

Headquarters &
Americas Operations

www.globalis.com

Middle East, Africa
& Asia Operations

www.alistech.ae