

SmartSource® Pro Elite

globalis
international



The SmartSource Pro Elite includes all the features that make a scanner ideal for teller and remote deposit capture applications, including a small footprint, durable design, high-speed capture, and industry-leading MICR accuracy and image quality on checks and other documents.



ID CARD SCANNING

Features two-sided ID card capture using 600 dpi image sensors that produce high-resolution color or grayscale images.

AUTOMATED CLEANING

Proper cleaning is the easiest – but most effective – way to prevent paper jams, double-feeds, image-quality problems, and unnecessary repairs on your scanners. Digital Check's automated cleaning feature makes it simple by giving a mechanical assist to your front-line operators.

An indicator light alerts users when it is time to clean. Use the Smart Button to activate cleaning mode, insert a cleaning card and the scanner performs a unique cleaning sequence that scrubs the track and cleans the sensors.



KEY FEATURES & BENEFITS

- › Batch-Feed - Scans up to 75 or 170 DPM
- › 1-to-4-Line Inkjet Endorser
- › Automated Cleaning with Smart Button Indicator
- › ID Card Scan
- › E13B and CMC7 MICR Recognition with Auto-Detect and integrated E13B
- › Optical Recognition Assist
- › Smart Button Combines Power Switch, Feeder Start/Stop, Cleaning Mode and LED Status Light



FAST & POWERFUL BATCH-FEED SCANNING

The Pro Elite is powerful enough for teller capture or branch capture, yet versatile enough for a small business. The Pro Elite features a 100-item input hopper and a top speed of up to 170 documents per minute, making it an ideal check scanner for medium to high-volume check scanning environments.



QUALITY & PERFORMANCE

The new SmartSource Elite series is a family of compact desktop check scanners, optimized for bank front-counter use as well as remote deposit capture. Like all scanners in the Digital Check® portfolio, the SmartSource Elite family provides industry-leading quality and performance.



INDUSTRY-LEADING IMAGE & MICR CAPTURE

The Pro Elite uses 600 dpi image sensors and applies thresholding to create high-resolution images resulting in superb CAR/LAR read rates. Our top-of-the-line MICR read heads coupled with optical recognition offer a proven and reliable defense against ambiguous characters and out-of-spec documents.



Let's get in touch!
info@globalis.com

Headquarters &
Americas Operations

www.globalis.com

Middle East, Africa
& Asia Operations

www.alistech.ae

Technical Specifications

SmartSource®
Pro Elite

Scanner Dimensions

Height 6.99 in (17.8 cm) **Width** 5.93 in (15.06 cm)
Length 8.66 in (22 cm) **Weight** 4.7 lbs. (2.1 kg)

Scan Speeds - Documents Per Minute (DPM)

USB Mode: Up to 75 or 170 DPM

Document Input and Output Pockets

Entry Pocket Up to 100 item hopper capacity
Entry pocket automatically opens for ease of use
Double-feed document detection
Exit Pocket Up to 150 items

Document Handling

Document Height 2.00 to 6.00 in (5.08 to 15.24 cm)
Image Capture Height Up to 4.25 in (10.80 cm)
Document Length 2.90 to 9.25 in (7.37 to 23.5 cm)
Document Weight 16 to 28 lb (60 to 105 gsm)
Document Thickness 0.0032 - 0.0058 in (0.081 - 0.147 mm)
Front ID Input ID cards and items up to 3.375 x 2.25 in (85.60 x 57.15 mm)
ID Card Capture (supported by application)

Inkjet Endorser

User-replaceable cartridge (600 dpi printing, 1-4 lines)
Three (3) levels of print quality available (economy, standard, or premium)
User-programmable text

Image Sensor

Resolution 600 dpi
Light Source Tri-Color LEDs

Image Compression Standards

CCITT Group 4 (bi-tonal images)
JPEG Baseline (gray level images)
JPEG Compression (color images)

MICR/OCR Recognition

E13B and CMC7 auto-sensing
OCR-A, OCR-B, E13B
Two (2) 0.50-inch OCR scan bands provided
96 Characters per scan band
MICR/OCR combined read

Productivity Functions (Smart Button)

Multi-colored LED status light, combined power switch, feeder start/stop, clear document jam, and activate cleaning mode

Connectivity

High-speed USB 2.0 cable and power supply included

Application Programming Interfaces (API)

SmartPVA API
Ranger Transport API (purchased separately from Silver Bullet Technology Inc.)

Supported Operating Systems

SmartPVA for Windows
Windows 11, Windows 10 (32/64 bit)
Ranger Transport API

Standard Warranty

One year

Power Requirements

100-240 VAC @ 50/60 Hz
Operating Power 48 W
Standby Power 3 W

Environmental

Operating Temperature 60° - 90° F (15° - 32° C)
Operating Humidity 35 - 85% non-condensing

Certifications

Safety UL, cUL, CE, BIS
Emissions FCC: Class A, ICES-003, CE, VCCI
Power Supply Efficiency DOE Level VI
RoHS Compliant



Part Numbers

SSP1-ELITE75 (Pro Elite 75 DPM model)
SSP1-ELITE155 (Pro Elite 170 DPM model)



Let's get in touch!
info@globalis.com

Headquarters &
Americas Operations

www.globalis.com

Middle East, Africa
& Asia Operations

www.alistech.ae