



>> Compact printer for general purpose
and specific applications

Dot Matrix Printers



Impact 3336 Plus

Reliable compact printer that delivers high print quality at speed reaching 540 cps. Globalis 3336 Plus provides advanced paper handling to support the largest variety of papers. It is ideally suited for business and industrial working environments where reliability, speed and quality are critical factors.

KEY FEATURES

- Print speed up to 540 cps
- 400 million strokes per wire print head life
- Up to 360 x 360 dpi print resolution
- 10 million characters ribbon life
- Up to 6 copies
- Up to 128 KB input buffer
- 20,000 hours MTBF
- Advanced paper handling for trouble-free use of continuous forms
- Standard Parallel and USB interfaces and optional serial interface
- Integrated LAN (option)
- Ideally designed for Continuous forms, Adhesive slip, Multicopy parts.
- Available with built-in Arabization for full Arabic standard support

Reliable mechanism

Impact 3336 Plus features an advanced tractor mechanism that allows flexible paper manipulation from: front in/top out, rear in/top out and from bottom in/top out. The impact 3336 Plus comes standard with a powerful 24-pin print head that functions on different types of paper using a wide range of fonts, character sets and barcodes.

Outstanding performance

The Impact 3336 Plus printer is designed to offer the best print techniques for a good quality output at a minimum cost. It delivers the same quality output on single sheets as well as on multiple copy forms up to 1+5 copies.



Print technology	24-pin, serial impact dot matrix												
Bilingual print speed	<table><tr><th>Max</th><th>HSD</th><th>Draft</th><th>LQ</th></tr><tr><td>12 cpi</td><td>540 cps</td><td>435 cps</td><td>145 cps</td></tr><tr><td>10 cpi</td><td>480 cps</td><td>360 cps</td><td>120 cps</td></tr></table>	Max	HSD	Draft	LQ	12 cpi	540 cps	435 cps	145 cps	10 cpi	480 cps	360 cps	120 cps
Max	HSD	Draft	LQ										
12 cpi	540 cps	435 cps	145 cps										
10 cpi	480 cps	360 cps	120 cps										
Character sets	Host code sets: ASMO-449/449+, ASMO- 708/708+, ARCII, ASCII, DEC/8/ASMO, Al-Arabi, IBM APC, XBASIC, CODAR-UFD, ICL CODAR, ICL ASMO-708, Cross Range, NCR 64/96, Data General, HP Arabic-8, HP Enhanced, Comterm 341/348/ 541, Integro 708 UNIX, ASMO/French, French/ASMO, User-defined PC code sets: ADOS-708/709/710/711/720/128 864/96, Mussaed Arabi, Arabic Windows 1256, IBM437, IBM851, IBM864												
Operating mode support	8-bit Arabic with neutrals, GLCCs, & GLCCs balancing 7-bit Arabic with GLCCs, GLCCs balancing, & escape sequences												
Arabic fonts	Naskh Draft, Naskh NLQ												
Latin fonts	Draft, Roman, Sans Serif, OCR-A, OCR-B, etc.												
Bar codes	8 types including EAN-13, Code 39, Code 128												
Print characteristics	Width: Cut Sheet: 148 - 420 mm Continuous paper: 101-406 mm Length (cut sheet): up to 364 mm Thickness: 0.065 to 0.52 mm												
Number of copies	Original + 5												
Print resolution	360 x 360 dpi												
Number of columns	136 col.												
Paper Insertion	Cut Sheet: Front in/Top Out Rear in/Top Out Continuous: Front in/Top Out Rear in/Top Out Bottom in/Top out												
Emulation	Epson ESC P, OKI												
Interface and connectivity	Parallel and USB interface (standard) Optional: Serial Optional: Integrated Ethernet LAN 10/100 Base T												
Input data buffer	Up to 128 Kb												
Consumables	Type: Black ribbon cartridge Life: 10 million characters												
Print head life	400 million strokes per wire												
MTBF	20,000 hours												
Physical	Dimensions (w x d x h): 623 x 395 x 173 mm Weight: 13 kg												
Operating environment	Temperature: Operating: 5° to 35° C; Storage: -20° to 60°; Humidity: 20% to 80% (operating); Consumptions: 15W to 75W; Acoustics: 56 dBa; Voltage: 220 v, 165 to 264 VAC; Frequency: 49.5 to 60 Hz												
Warranty	Standard one-year												

