

## CF 120A3

#### Ideal for:

- Integration in production lines
- A3 label printing (e.g. in paper mills)
- Business and workflow documents
- Month end invoice runs

### **HIGHLIGHTS / FEATURES / SPECIAL ATTRIBUTES**

- Minimal downtime and extremely long maintenance intervals
- > Toner refill possible during operation
- Extremely fast printing speed
- Flexible expansion options for paper feed and tray
- Duplex printing at full printing speed
- Optional IPDS emulation making it the printer of choice for IBM solutions

# HIGHEST PERFORMANCE FOR BUSINESS, LOGISTICS AND PRODUCTION



**CF 120A3** 

When highest printing performance really matters, the CF 120A3 is the perfect choice: the lightning-fast printing speed of up to 120 A4-pages a minute and extremely long maintenance intervals predestine this model for deployment in print-intensive business and logistics applications. Face-up output as well as SPS control and Status Out options ensure the optimal prerequisites for integration in production lines. The CF 120A3 combines highest levels of reliability with versatile paper handling capabilities.

#### **Print Engine**

Print technology Laser, OPC

heat / pressure

Controller MPC 3.6

**Print speed** up to 120 pages/minute (A4)

up to 54 pages/minute (A3)

**Print resolution** max. 600 dpi x 600 dpi

**Duty cycle** up to 400.000 pages (A4 landscape)

(based on a using period of 60 months)

max. 500.000 pages (A4 landscape))

Power supply 220-240 V /50 HZ

Power consumption 13A

Dimensions (WxDxH in mm) 870 x 760 x 980 (printer only)

1080 x 810 x 1190 mm (incl. Display)

Weight ca. 300 kg (without options)

**Environment temperature** 10 - 30°C

Relative humidity 20 - 85 % (rel., non condensing)

Interfaces

IEEE 1284 (Centronics) Ethernet-Interface

10/100/1000 MBit, bi-directional (TCP/IP)

Memory RAM: 2GB

Flash: 50MB

#### MPC 3.6 High-End Print-Controller

#### **Emulations**

MICROPLEX IDOL, HP-PCL5/ HPGL, AGFA Reno, µ-Postscript, LN03+, BULL-MP6090, Etimark MP-1220, TEC Bx72, TEC B6xx, Diablo 630, IBM Proprinter, EPSON FX-80 (ESC/P), MT-600/MT40, IDS, ANSI Genicom, TIFF, XML (SAP® RFID), CUPS Raster, RFM, TN3270 (Telnet terminal emulation)

#### **Optional Emulations**

CODE-V (Magnum), XEROX XES, KODESCRIPT+, Prescribe/PSB 2, IGP-10, IGP/PGL, Datamax, Labelpoint, LDC, ZPLII, EPL 2, UPI Fingerprint, IER Command, cab, Godex EZPL, Barcode 2, HP Designjet, IPDS, AEA, AFP, Status-Out, PDF, TN3270 (Telnet terminal emulation) (more emulations on request)

#### Barcodes

Codebar, Code39, MSI, PDF417, Interleaved 2/5, Interleaved 2/5 (3-Strich Datalogic), Interleaved 2/5 (3-Strich Matrix), EAN-8, 13, 128, Add-On-Codes, Code11, Code93, Code 128, UPC-A, UPC-E

#### **Optional Barcodes**

Datamatrix, Maxi-Code, QR Code, Aztec-Code, USD-5 (more barcodes on request)

Additional functions

**Network capabilities** authentication standard IFFF 802.1x

on-the-fly in the printer Intelligent barcode generation

Format splitting in several subformats by command

flash memory for forms and fonts inside the printer Integrated form management

#### **Optional functions**

#### Status-out

gives notice of each correctly printed page via interface. Further features can be found in the manual.

#### Programmable GPIO-Interface (SPS-Control)

EMBEDDED INTELLIGENCE – Enabling two-way communication between printer and a PLC. Integration of the printer into production lines is possible, controlled by GPIO-interface Customer / Application specific modifications possible.

#### **SPECIFICATIONS**




#### Printable Media

Size A5R\* - A3W\*

Weight 60 to 220 g/m<sup>2</sup> max. 300 g/m

(option 3430 is required)



#### **Paper Path**

1+2: 1.200 and 800 sheets (A4/Letter) cassette 3: 500 sheets (B5R\* bis A3W\*\*) cassette 4: 500 sheets (A5R\* to A3W\*\*)

#### Optional

up to 3.500 sheets A4, B5 (3433) up to 5.000 sheets [3430]

(each 2.500 sheets in bin 5 and 6, 7 and 8)

 $\Delta 3W^{**} - \Delta 5R^{*}$  (no offset)

#### Output

faceup / face down

#### Optional

finisher saddle stitching (3440) 4000 sheets, 100-sheets-stitching A3 - B5R\* (offset/stitching), A3W\*\* - A5R\*

(no offset) (more options on request)

\* R = short side feeding \*\*A3W = 12" x 18" (304mm x 457mm)

