



- Single-feed, Fast and Quiet Scanning
- 1-Line Inkjet Endorser Option
- Simple to Operate
- Engineered for Durability
- Ultraviolet Image Capture Option
- E13B and CMC7 MICR Recognition with Auto-Detect and integrated E13B Optical Recognition Assist

The award-winning CheXpress CX30 is the only bank-quality check scanner offered at a small business price. This stylish and quiet single-feed scanner is the perfect device for lower volume check capture environments.

Worry-Free Reliability

Our scanners are engineered to last. The CX30 will process over a million items during its life, which is the highest duty cycle of any scanner in its class.

The Ultimate in Low Maintenance

Maximize productivity and avoid hardware headaches. The CX30's simple transport design means minimal user maintenance is required.

Extremely Fast, Remarkably Quiet

At a rated speed of one second per scan the CX30 makes quick work of any deposit. Concerned about noise? Don't be. The CX30 is remarkably quiet and suited for any work environment.

Here, There, Anywhere

We know desktop real estate is at a premium. The CX30's economical footprint and flexible cable management system means you won't have an issue finding it a home in your workspace.

Pass Through Feed Option

Users can choose between "scan and return" or "pass through" scan modes. With "pass through", scanned items follow a straight paper path and exit through the rear of the scanner. Ideal for kiosks and other self-service settings.

Image and MICR Quality is Everything

Featuring high performance front and rear image sensors with dual pass MICR read-head capability, the CX30 is truly in a class of its own. With our special document handling technologies, even the most challenging money orders and checks written with gel pen ink are a snap to process.

The Secure Choice for Banks Around the World

The CX30 is the secure choice for banks around the world because of its reliability and image quality. Whether you are a small business processing a few checks per day or a larger merchant that receives dozens of checks per day, the CX30 is built to handle whatever you throw at it. That's why banks around the world prefer the CX30, knowing that their brand will be well-represented and their customers well-served by this intuitive and reliable scanner.

PRODUCT SPECIFICATIONS

Scanner Dimensions

Height: 7.47 in (18.97 cm)
Width: 3.92 in (9.96 cm)
Length: 9.38 in (23.83 cm)
Weight: 3.95 lbs. (1.80 kg)

Scan Speeds - Documents Per Minute (DPM)

Up to 30 DPM

Document Input and Output Pockets

Entry Pocket: 1 item
Double document detection
Exit Pocket: Up to 5 items

Document Handling

Document Height: 2.12 in - 4.25 in (54 - 108 mm)
Image Capture Height: Up to 4.17 in (106 mm)
Document Length: 3.19 in - 8.98 in (121 - 228 mm)
Document Weight: 16 - 28 lb. bond (60 - 105 gsm)
Document Thickness: 0.0032 in - 0.0058 in
(0.081 - 0.147 mm)

Endorsement Option

User-replaceable cartridge (96 dpi printing, 1-line)

Franker Option

User replaceable red ink stamp

Image Sensor

Resolution: 300 dpi
Light Source: Tri-Color LEDs
Optional Front Ultraviolet (UV) Image Sensor

Image Compression Standards

JPEG (24 bit color, 8 bit grayscale)
BMP (24 bit color, 4 or 8 bit grayscale)
TIFF Group 4 B/W

MICR Recognition

(Magnetic Ink Character Recognition) for E13B and CMC7
Optical Character Recognition to enhance MICR Read,
further enhanced using DCC's Best Read™ API function

Connectivity

Mini-B USB 2.0 cable and power supply included

Application Programming Interfaces (API)

DCC API 10.09 or newer
SecureLink 2.0 API (Requires SecureLink External Device)

Supported Operating Systems

Windows 8®, Windows 10® (32/64 bit versions)
Mac OS and Linux
(Contact Digital Check Technical Support for specific versions supported)

Standard Warranty

1 year depot warranty

Electrical

Power Consumption: 24 Watts
Input Voltage: 100 to 240 VAC, 50/60 Hz
Separate Standard Power Supply: Auto sensing for voltage

Environmental

Operating Temperature: 60° - 90° F (15° - 32° C)
Operating Humidity: 35 - 85% non-condensing

Certifications

Safety: UL, cUL, CE
FCC: Class B (Industrial, Business or Home)
EMC: IEC CE
Efficiency: CEC V 115V - Power Supply
RoHS Compliant



HEADQUARTERS:

Globalis International, Montreal, Canada
info@globalis.com | www.globalis.com

REGIONAL HEADQUARTERS:

Alistech Trading LLC, Dubai, UAE
info@alistech.ae | www.alistech.ae