

## **SmartSource®**

### Pro Elite



#### SmartSource Pro Elite

Digital Check, the recognized world leader for payment-related products and services, offers the SmartSource Pro Elite, a compact-size scanner optimized for front counter and remote deposit capture solutions. Like all scanners in the Digital Check portfolio, the SmartSource Pro Elite provides industry-leading quality and performance.

#### Elite – The Best of the Best

As the name implies, the SmartSource Pro Elite incorporates the best features of the highly popular SmartSource

Professional Scanner. In addition, several exciting new features such as ID card and tall document scanning have been incorporated into this design.

#### **Small Package**

The SmartSource Pro Elite has one of the smallest footprints in the industry. Its output pocket is 50% larger than competitive devices – enabling the processing of imperfect documents that jam in scanners with smaller pocket designs.



#### **Digital Check Quality**

Do not let the size fool you. The Digital Check SmartSource Pro Elite scanner provides the industry-leading quality and performance that Digital Check is known for, including:

- High speed
- Image quality
- MICR performance
- Paper handling
- Reliability

#### SmartSource Pro Elite Technical Information

Document Processing Throughput	Single Output Pocket
ocument throughput of 75 or 155 documents per minute	150 item pocket capacity
Power Requirements	Automatic Document Feeder
100-240 VAC @ 50/60 Hz Operating Power:  20 W Standby Power:  3 W	Up to 100 item hopper capacity Automatically opens for ease of use Double document detection
Weight	Dimensions
Installed weight: 4.7 lbs (2.1 kg) Power supply: 0.55 lbs (0.25 kg)	Length: 8.86 in (22.5 cm) Depth: 5.39 in (13.7 cm) Height: 6.99 in (17.8 cm)
Certifications	Magnetic Ink Character Recognition (MICR)
CE, UL/TUV, CSA, RoHS, VCCI, FCC Class A 2010 Appliance Efficiency Regulations, California, Title 20	E13B and CMC7 read with auto-detect
Document Sizes	Image Capture
Document size  - Height: 2.00 to 6.00 inches (5.08 to 15.24 cm)  - Imaged height: 4.25 inches (10.80 cm)  - Length: 2.90 to 9.25 inches (7.37 to 23.5 cm)  (Adding Machine Tape Mode supports up to 6 feet)  Document weight  - Paper weight: 16 to 28 lb (60 to 105 gsm)  - Accepts 12 lb (45 gsm) paper at a reduced throughput & pocket capacity  - Alternate input accepts ID cards & other media up to 0.030 inches thick	Front and rear image capture at 300 dots per inch (dpi) Up to five (5) images Image renditions available - Bi-tonal (black/white) - Gray level (256 gray shades) - Color (24-bit) (reduced throughput) Image resolutions available - 300 dpi, color only (reduced throughput) – Device Suite only - 240, 200 dpi, color, gray level or bi-tonal - 120, 100 dpi, gray level
Communication Interface	Image Compression Standards
USB 2.0 high-speed	CCITT Group 4 (bi-tonal images)  JPEG Baseline (color and gray level images)  Uncompressed 24-bit, RGB pixel data (color images) – Device Suite only
Operating Systems	Operator Interface
Windows 10 Professional 32 and 64-bit Windows 8 Professional 32 and 64-bit Windows 7 Professional 32 and 64-bit	Combined power switch, feeder start/stop and SmartClear button Light Emitting Diode (LED)
Rear Endorsement	Optical Character Recognition (OCR)
Ink jet print cartridge (600 dpi) One (1) to four (4) line endorsement, any True Type font Graphics capable for logos and signatures These (2) leads of prints with (as true to be dead or as	OCR-A, OCR-B, E13B, and barcode fonts supported Two (2) 0.50 inch OCR scan bands provided 96 characters per scan band

## Three (3) levels of print quality (economy, standard, or premium) Application Programming Interfaces (API)

CAPI (Common Application Programming Interface) Device Suite Ranger® for SmartSource (purchased separately from Silver Bullet)

NOTES: Not every API Operating System combination may be qualified. Contact your application provider for more information.

Specific capabilities may not be supported by every API or will require a minimum API version. Contact Digital Check for more information.

MICR/OCR combine read

# For more information about the entire line of Digital Check remote capture products, call 1-847-446-2285 or visit www.digitalcheck.com

SmartSource and ReceiptNOW are registered trademarks of Digital Check Corp. Ranger is a registered trademark of Silver Bullet Technology, Inc. All other brands and products referenced in this document are acknowledged to be the trademarks or registered trademarks of their respective holders. Specifications are subject to change without notice.



**SmartTIP** For more information use your smartphone and snap a photo.

