

TellerScan® TSX40

The Secure Choice

globalis
international



Built with best-of-breed features from both the award-winning CheXpress® and TellerScan scanner families, Digital Check's TellerScan TSX40 provides bank-quality scanning at a low cost. Created specifically for remote deposit capture or teller environments that require an economical batch-feed scanner, the TSX40 also includes premium features typically found on more expensive models.



ID SCANNING

The TSX40 features two-sided full-color ID card capture utilizing 600 dpi image sensors that produce high-resolution color or grayscale images.

FAST BATCH-FEED SCANNING

The TSX40 can feed batches of up to 30 checks (and store up to 50 items in the exit pocket) and scan at speeds of up to 40 documents per minute. The TSX40 will efficiently handle your business deposits with Digital Check MICR accuracy and image quality for higher CAR/LAR read rates.

AUTOMATED CLEANING

The TSX40 alerts the user via an LED light when it is time to clean. The user then simply presses the Smart Button three times to activate cleaning mode, inserts a fresh cleaning card, and the scanner performs a unique cleaning sequence that scrubs the track and cleans the sensors.

KEY FEATURES & BENEFITS

- › Batch Feed - Scan Speeds up to 40 DPM
- › ID Card Scanning
- › Single-Line Rear Endorsement
- › Optional Franker
- › Optional Ultraviolet Image Capture
- › Bank-Quality Scanner at an Affordable Price



THE SECURE CHOICE FOR BANKS WORLDWIDE

Digital Check is The Secure Choice® for banks and businesses both domestically and internationally. The TSX40 is built from more than 60 years of experience developing image capture solutions. This scanner will be a workhorse for your business, providing years of worry-free check capture.



ULTRAVIOLET (UV) IMAGE CAPTURE OPTION

UV scanning has been a standard in international markets to help in the detection of potentially fraudulent checks. The TSX40 is available with UV image sensors able to capture images in 256 grayscale, bitonal, or reverse bitonal images with both UV and "white" lights on. The TSX40 is able to capture UV images at up to 40 DPM — no loss of speed.



INDUSTRY-LEADING IMAGE & MICR CAPTURE

The TSX40 uses 600 dpi image sensors and applies thresholding to create high-resolution images resulting in superb CAR/LAR read rates. Our top-of-the-line MICR read heads coupled with optical recognition offer the best defense against ambiguous characters and out-of-spec documents.



Let's get in touch!
info@globalis.com

Headquarters &
Americas Operations

www.globalis.com

Middle East, Africa
& Asia Operations

www.alistech.ae

Technical Specifications TellerScan® TSX40

Scanner Dimensions

Height 7.56 in (19.2 cm) **Width** 5.08 in (12.9 cm)
Length 12.13 in (30.8 cm) **Weight** 4.45 lbs. (2.02 kg)

Scan Speeds - Documents Per Minute (DPM)

Up to 40 DPM

Document Input and Output Pockets

Entry Pocket Up to 30 items
Double-feed document detection
Exit Pocket Up to 50 items

Document Handling

Document Height 2.00 to 6.00 in (5.08 to 15.24 cm)
Image Capture Height Up to 4.17 in (106 mm)
Document Length 3.25 in - 9.5 in (82.55 - 241.3 mm)
Document Weight 16 - 28 lb. bond (60 - 105 gsm)
Document Thickness 0.0032 in - 0.0058 in
(0.081 - 0.147 mm)
ID Cards must conform to ISO/IEC 7810 standard
(ID-1 Size and NON-Embossed)

MICR Recognition

(Magnetic Ink Character Recognition) for E13B and CMC7 Optical Character Recognition to enhance MICR Read, further enhanced using DCC's Best Read® API function

Endorsement Option

User-replaceable ink cartridge (96 dpi printing, 1-line)
User-programmable text

Image Sensor

Resolution 600 dpi
Light Source Tri-Color LEDs
Optional Front Ultraviolet (UV) Image Sensor

Franker Option

User-replaceable red ink stamp

Image Compression Standards

JPEG (24-bit color, 8-bit grayscale)
BMP (24-bit color, 4 or 8-bit grayscale)
TIFF Group 4 B/W

Productivity Functions (Smart Button)

Power on/off, Cleaning mode activation, Item eject

Connectivity

USB 2.0 cable and power supply included

Application Programming Interfaces (API)

DCC API
DCC API 12.12 or newer for UV Scanning

Supported Operating Systems

Windows 11, Windows 10 (32/64 bit)
Mac OS and Linux

Standard Warranty

One year

Electrical

Power Consumption 48 Watts
Input Voltage 100 to 240 VAC, 50/60 Hz
Separate Standard Power Supply Auto sensing for voltage

Environmental

Operating Temperature 60° - 90° F (15° - 32° C)
Operating Humidity 35 - 85% non-condensing


Certifications

Safety UL, cUL, CE
Emissions FCC: Class B, ICES-003, CE
Power Supply Efficiency DOE Level VI
RoHS Compliant



Part Numbers

156000-01 (TSX40 standard model)
156000-02 (TSX40 with inkjet endorser)
156001-02 (TSX40 with inkjet endorser and franker)
156005-02 (TSX40 with inkjet endorser and UV sensors)



Let's get in touch!
info@globalis.com

Headquarters &
Americas Operations

www.globalis.com

Middle East, Africa
& Asia Operations

www.alistech.ae