

# Globalis Impact 1082



## Compact printer for general purpose and specific applications

**Globalis Impact 1082** comes in a compact design and prints up to 454 Characters per second at very low noise level.

The Flatbed printer is ideal for business applications as well as industrial environments, offering an all-in-one solution for transactional single sheet applications as well as continuous form printers with outstanding multi-copy capacity.



## Key Features

- › Print speed up to 454 cps
- › 82 column flatbed printer
- › Printhead life of 400 million strokes / wire
- › Original + 6 copies
- › 24-pin impact dot-matrix
- › 128 Kb buffer
- › 8 barcode types
- › Flexible and intelligent printer that can be used for all business applications
- › Bi-directional printing with logic seeking
- › Standard parallel. Serial, LAN or USB interface available
- › Suitable for transaction applications
- › 10 million characters ribbon

**Let's get in touch!**

info@globalis.com

Headquarters &  
Americas Operations

[www.globalis.com](http://www.globalis.com)

Middle East, Africa  
& Asia Operations

[www.alistech.ae](http://www.alistech.ae)

# Technical Specifications

## Globalis Impact 1082

### Printing

**Print Technology**

24-pin impact dot-matrix

**Print Direction**

Bi-directional printing with logic seeking

**Printable Columns**

82 characters @ 10CPI

**Print Speed**

> 12 CPI

HSD: 454 CPS · Draft: 345 CPS · LQ: 115 CPS

> 10 CPI

HSD: 300 CPS · Draft: 250 CPS · LQ: 75 CPS

**Print Language/Emulations**

ESC/P-K Emulation, OKI Emulation (optional), AR Emulation (optional) or custom

### Paper Handling

**Types**

Cut Sheet, Continuous Paper, Multi-part Forms, Envelope, Post Card, Adhesive label

**Width**

**Cut sheet:** 65~298 mm

**Continuous Paper:** 50~286 mm

**Length**

**Cut sheet:** Min 52 mm

**Continuous Paper:** Min 52 mm

**Thickness**

0.06~0.09 mm, Adaptive paper thickness

**Paper Path**

**Friction feed:** front in front out, front in rear out

**Tractor feed:** rear in front out

### Dimension & Weight

**Width, Depth & Height:** 390×193×187 mm

**Weight:** Approx. 4 kg

### Character Specification

**Character Sets**

ASCII, Italic, PC437, PC850 etc.  
15 International Character sets

**Font**

Draft, Roman, Sans Serif, OCR-A, OCR-B etc.

**Bar Code Font:** 8 sets including EAN-13, Code 39, Code 128 etc. · 2-Dimension code

### Other Specifications

**Copy Capability**

Original + 4 copies

**Interface**

Parallel\*, USB interface (USB2.0), Serial\*, LAN\*, WIFI\*, Bluetooth\*. (\*Optional).

**Buffer** 128K Bytes

**Reliability**

**MTBF:** 30,000 hours

**Print Head Life:** 400 millionstrokes/wire

**Ribbon**

Approx. 6 million characters

**Environment Condition**

**Temperature:** 5~40 °C · **Humidity:** 20%~80% RH

**Voltage** 110V/220V

**Operation System**

Windows 9X/2000/XP, Win 7, Unix, Linux, etc.

**Certificates**

- > CCC (China Compulsory Certification)
- > EMC: GB9254
- > China Certificate for Energy Conservation Product
- > China Environmental Labeling Product Certificate



Let's get in touch!

info@globalis.com

Headquarters &  
Americas Operations

[www.globalis.com](http://www.globalis.com)

Middle East, Africa  
& Asia Operations

[www.alistech.ae](http://www.alistech.ae)