

SmartSource®



SmartSource ReceiptNOW Elite Available in USB and Ethernet



SmartSource ReceiptNOW

Available in USB and Ethernet

Our Customers Say it Best!

"Integrating the ReceiptNOW printers and SmartSource scanners enabled us to deliver an enhanced client experience while capitalizing on processing efficiencies." – Rachel Emery, AVP Office Automation Manager, United Bank & Trust

SmartSource ReceiptNOW

Prints receipts right at your check scanner. Engineered to fit under Digital Check SmartSource scanners – combining scanner and receipt printer units into one footprint, saving valuable counterspace!

SmartSource ReceiptNOW — Designed to fit under the SmartSource Professional, Value, Expert, Adaptive, and other scanners.

SmartSource ReceiptNOW Elite — Engineered to fit beneath the SmartSource Elite series scanners.

SmartSource ReceiptNOW Ethernet Elite —

Engineered to fit beneath the SmartSource Elite series scanners and network-enable your printer. This printer includes both an Ethernet and USB connection, and can operate in either environment.

Features

- Quiet thermal receipt printer
- Frees up teller space
- Simple pull-out, drop-in paper
- Largest paper roll
- Full or partial paper cut

- Fast 8 inches/second (20 cm/second) delivery
- Less maintenance than matrix printers
- Fast installation for existing sites
- Three-year warranty (advanced exchange available)

Compatibility

- USB or Ethernet interface
- Full 108 std & international fonts w/barcode
- Prints on standard, security, non-BPA and 2-color paper
- International power compliant
- · Worldwide certifications

Customizable Teller Receipts

- Top/bottom logos
- Border messages
- Watermarks
- Windows True Type fonts
- Color text/graphics using 2-color paper



SmartSource ReceiptNOW Technical Information

Models

SRNELITE-USB - ReceiptNOW Elite, USB Interface

SRNELITE-ETH - ReceiptNOW Elite, Ethernet Interface

SRN2PTR-USB - ReceiptNOW, USB Interface

SRN2PTR-ETH - ReceiptNOW, Ethernet Interface

Printing/Feed/Cut

Direct Thermal Printer

Black and Two Color Capability

Black Print Speed 8 inches/second (20 cm/second)

Resolution: 203 x 180 dpi

95 Alphanumeric, 13 International Characters w/Kanji

True Type Fonts available when being driven as a Windows printer

1D/2D Bar Code Fonts 512K on-board Logo Flash Full/Partial Auto Cutter

Controls

On/Off Switch

Paper Empty/Low LED's w/Audible Alerts

Paper Feed Button

Paper Width Adjustment

Power indicator

Interface

USB or Ethernet Models Available Standard ESC/POS Command Set

OPOS & JavaPOS, Auto Status Back (ASB)

Dimensions

	ReceiptNOW	ReceiptNOW Elite
Height:	5.4 inches (13.7 cm)	5.2 inches (13.2 cm)
Width:	6.1 inches (15.5 cm)	5.7 inches (14.5 cm)
Length:	15.3 inches (38.8 cm)	9.5 inches (24.2 cm)

Environment/Acoustics

5~50°C Operating Environment Acoustics < 60 dba Cutting or Printing









Powe

International Power 100-240VAC, 50/60Hz

Power Supply Included

Paper/Loading

Standard, Security, Non-BPA, 2-Color Paper 2.4 in. to 3.25 in. (6.1 cm to 8.3 cm) Paper Widths - Adjustable Largest 3.25 in. (8.3 cm) Diameter Paper Roll

Slide Out Tray, Drop-in Paper

Warranty/Service

3 Year Warranty

Advanced Exchange Available

Graphic Receipt Customization

Multiple Graphics Can be Placed Anywhere

Custom Messages Watermarks

Host OS

Windows 10 (32/64), Windows 8 (32/64)

Maintenance

Print Exerciser & Diagnostic Software

Operator Guide

Certifications

FCC Class B, CE, VCCI, for EMI Emissions

CE, for Susceptibility and ESD

CE, CB, CUL/UL 60950, for Safety

RoHS Compliant (EU)

2010 Appliance Efficiency Regulations, California, Title 20

NOTE: Not every API Operating System combination may be qualified. Contact your application provider for more information. Specific capabilities may not be supported by every API or will require a minimum API version. Contact Digital Check for more information.

